


Adresse/Société/Adress:

Auftrag/Affaire/Task:


Datum/Date/Date:

Position Repérage Client Position	Form Forme Form A - D	Typ Type Type A - H	Profil/Référence profil/Profile			Radius Aussen Körper Rayon ext. le corp Radius outside profile R	Sehnenlänge Corde Chord length 1	Stichhöhe Flèche Height 2	Schenkellängen Surlongueur Straight legs 3	Menge Quantité Quantity
			A	B	C					


Form A




Form B



Form C



Form D




Andere Profiltypen sowie
im Grundriss gebogene Profile
auf Anfrage.


Autres types de profilés et
profilés au tracé cintré
sur demande.

Other profile types and
profiles curved in the floor plan
are available on request.


Typ A




Typ B




Typ C




Typ D




Typ E




Typ F



Typ G



Typ H



Profil Profilé Profile	Min. Radius Rayon min. Min. radius R
	
600.002 Z	350 mm
600.005 Z	700 mm
600.006 Z	300 mm
600.007 Z	900 mm
600.008 Z	300 mm
600.010 Z	600 mm

	
601.635 Z	300 mm
601.685 Z	600 mm

	
602.635 Z	600 mm
602.685 Z	1100 mm

	
603.635 Z	600 mm
603.685 Z	850 mm

	
605.635 Z	600 mm
605.685 Z	900 mm

Profil Profilé Profile	Min. Radius Rayon min. Min. radius R
	
630.010 Z	600 mm
630.013 Z	900 mm

	
630.110 Z	800 mm
630.114 Z	1000 mm

	
630.411 Z	800 mm
630.416 Z	1300 mm

	
630.900 Z	400 mm

Profil Profilé Profile	Min. Radius Rayon min. Min. radius R
	
601.635.6 Z	500 mm
601.685.6 Z	850 mm

	
602.635.6 Z	600 mm
602.685.6 Z	1100 mm

Stahl-Glasleisten Parcloles en acier Steel glazing beads	Min. Radius Rayon min. Min. radius R
	
402.112 Z	500 mm
402.115 Z	500 mm
402.120 Z	600 mm
402.125 Z	750 mm
402.130 Z	1000 mm
402.135 Z	1500 mm

Stahl-Glasleisten Parcloles en acier Steel glazing beads	Min. Radius Rayon min. Min. radius R
	
62.507 GV+GC	300 mm
62.508 GV+GC	300 mm
62.509 GV+GC	300 mm

Aluminium-Glasleisten Parcloles en aluminium Aluminium glazing beads	Min. Radius Rayon min. Min. radius R
	
404.112	400 mm
404.115	400 mm
404.120	400 mm
404.125	450 mm
404.130	500 mm
404.135	600 mm
405.115	500 mm
405.120	500 mm
405.125	800 mm
406.903	500 mm
406.905	500 mm
406.907	500 mm
406.909	600 mm