


Adresse/Société/Adress:

Auftrag/Affaire/Task:


Datum/Date/Date:

Position Repérage Client Position	Form Forme Form A-D	Typ Type Type A-H	Profil/Référence profil/Profile				Radius Aussen Körper Rayon ext. le corp Radius outside profile R	Sehnenlänge Corde Chord length 1	Stichhöhe Flèche Height 2	Schenkellängen Surlongueur Straight legs 3	Menge Quantité Quantity
			A	B	C	D					


Form A




Form B



Form C



Form D




Andere Profiltypen sowie im Grundriss gebogene Profile auf Anfrage.


Autres types de profilés et profilés au tracé cintré sur demande.

Other profile types and profiles curved in the floor plan are available on request.


Typ A




Typ B




Typ C




Typ D




Typ E




Typ F



Typ G



Typ H



Profil Profilé Profile	Min. Radius Rayon min. Min. radius R	blank brut bright	verzinkt zinguée galvanised	Profil Profilé Profile	Min. Radius Rayon min. Min. radius R	blank brut bright	verzinkt zinguée galvanised	Profil Profilé Profile	Min. Radius Rayon min. Min. radius R	Stahl-Glasleisten Parcloles en acier Steel glazing beads	Min. Radius Rayon min. Min. radius R	
		mm	mm			mm	mm		550 mm			
01.531	350			30.006	500	500		30.900		402.112 Z	500 mm	
01.534	400	800		30.007	550	550				402.115 Z	500 mm	
01.564	650	1050								402.120 Z	600 mm	
01.592	1100									402.125 Z	750 mm	
										402.130 Z	1000 mm	
										402.135 Z	1500 mm	
					700	700		Stahl-Glasleisten Parcloles en acier Steel glazing beads	Min. Radius Rayon min. Min. radius R	Aluminium-Glasleisten Parcloles en aluminium Aluminium glazing beads	Min. Radius Rayon min. Min. radius R	
02.531	350	600		30.106	700	700						
02.534	400	800		30.107	750	750		62.507 GV+GC	300 mm	404.109	400 mm	
02.564	650	1050						62.508 GV+GC	300 mm	404.112	400 mm	
400.023	800							62.509 GV+GC	300 mm	404.115	400 mm	
					700	700				404.120	400 mm	
				30.406	700	700				404.125	450 mm	
				30.407	750	750				404.130	500 mm	
	600									404.135	600 mm	
03.531	600											
03.534	500	800										
					600	900*					405.110	500 mm
				04.568	850						405.115	500 mm
											405.120	500 mm
											405.125	800 mm
											405.130	1000 mm
											405.135	1000 mm
											406.903	500 mm
											406.905	500 mm
											406.907	500 mm
											406.909	600 mm
											406.909	600 mm