


Adresse/Société/Adress:

Auftrag/Affaire/Task:


Datum/Date/Date:

Position Repérage Client Position	Form Forme Form A-D	Typ Type Type A-F	Profil/Référence profil/Profile			Radius Aussen Körper Rayon ext. le corp Radius outside profile R	Sehnenlänge Corde Chord length 1	Stichhöhe Flèche Height 2	Schenkellängen Surlongueur Straight legs 3	Menge Quantité Quantity
			A	B	C					


Form A




Form B



Form C



Form D




Andere Profiltypen sowie im Grundriss gebogene Profile auf Anfrage.


Autres types de profilés et profilés au tracé cintré sur demande.

Other profile types and profiles curved in the floor plan are available on request.


Typ A




Typ B




Typ C




Typ D



Typ E



Typ F



Profil Profilé Profile	Min. Radius Rayon min. Min. radius R	blank brut bright	verzinkt zinguée galvanised	Profil Profilé Profile	Min. Radius Rayon min. Min. radius R	blank brut bright	verzinkt zinguée galvanised	Stahl-Glasleisten Parcloses en acier Steel glazing beads	Min. Radius Rayon min. Min. radius R	Aluminium-Glasleisten Parcloses en aluminium Aluminium glazing beads	Min. Radius Rayon min. Min. radius R
	350	mm	mm		500	mm	mm	 402.112 Z 500 mm 402.115 Z 500 mm 402.120 Z 600 mm 402.125 Z 750 mm 402.130 Z 1000 mm 402.135 Z 1500 mm	500	 404.109 400 mm 404.112 400 mm 404.115 400 mm 404.120 400 mm 404.125 450 mm 404.130 500 mm 404.135 600 mm	400
01.634	350			30.018	500				400		
01.684	450		900	30.019	650				400		
									400		
									450		
	350		600		800			 405.110 500 mm 405.115 500 mm 405.120 500 mm 405.125 800 mm 405.130 1000 mm 405.135 1000 mm 406.903 500 mm 406.905 500 mm 406.907 500 mm 406.909 600 mm	500		
02.634	350		600	30.118	800				500		
02.684			1050	30.119	900				500		
									800		
									1000		
	1550				800			Stahl-Glasleisten Parcloses en acier Steel glazing beads	Min. Radius Rayon min. Min. radius R		
04.637	1550			30.419	1100				300		
									300		
	1550							 62.507 GV+GC 300 mm 62.508 GV+GC 300 mm 62.509 GV+GC 300 mm	300		
05.637	1550								300		
									300		
									300		
	800		1100*								
400.052	800		1100*								
			1000*								
400.054			1000*								
			700*								
400.055			700*								
	1100		1100								
81.010	1100		1100								

* GV+GC